

Borel

Standard Furnaces & Ovens

since 1918



Photos for illustration purposes only

BOREL LABORATORY LINE OVENS 300°C BLN 300

Definition: Natural convection electrical oven for all applications.

Construction: Stainless steel interior, multiple shelves supports.

Insulation: Rock wool insulation of all surfaces, including door.

Heating: Battery of shielded electrical resistors.

Electricity: Single-phase 230 VAC, 50 Hz.

Regulation: PID microprocessor. RS232 and USB interface. Software free to download on our website.

Documentation: CE marking and operating instructions in English.

Delivered with: 1 shelf. From 56 l, 2 shelves, and 3 shelves for 245 l.

Version: *-I models with inox housing.



MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
BLN 300-32	N19000	32	400 x 320 x 250	590 x 630 x 520	1.1	35
BLN 300-32-I	N19001	32	400 x 320 x 250	590 x 630 x 520	1.1	35
BLN 300-56	N19002	56	400 x 390 x 360	590 x 700 x 620	1.6	50
BLN 300-56-I	N19003	56	400 x 390 x 360	590 x 700 x 620	1.6	50
BLN 300-112	N19004	112	460 x 540 x 450	650 x 850 x 710	2.4	65
BLN 300-112-I	N19005	112	460 x 540 x 450	650 x 850 x 710	2.4	65
BLN-300-245	N19006	245	600 x 800 x 510	810 x 1200 x 770	3.0	126
BLN-300-245-I	N19007	245	600 x 800 x 510	810 x 1200 x 770	3.0	126

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com