

Borel

Standard Furnaces & Ovens

since 1918



Photos for illustration purposes only

CAR-HEARTH FURNACES 1200°C FM 1200

Definition: Chamber furnace with mobile hearth (trolley on rails).

Construction: Robust construction made of bent plate. Vertical lifting front door.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Aeration: Exhaust vent on top.

Heating: Coil resistors on ceramic tubes. The heating is turned off at the opening of the door.

Electricity: 3x400 VAC.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.

Delivered with: Removable ceramic sole.



MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
FM 1200-45	N16348	45	300 x 300 x 500	660 x 820 x 810	7.5	106
FM 1200-60		60	400 x 300 x 500	760 x 800 x 840	9.6	190

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com

* V 28.01.2022

Specifications subject to change