

Borel

Standard Furnaces & Ovens

since 1918



CHAMBER FURNACES 1500°C FP 1500

Definition: Electric chamber furnace for all applications, high temperature.

Construction: Robust construction made of bent plate. Vertical lifting front door.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Heating: Silicon carbide heating elements. The heating is turned off at the opening of the door.

Electricity: 3x400 VAC.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.

Delivered with: Removable ceramic sole.



Photos for illustration purposes only



MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
FP 1500-5	G15005	5.25	150 x 140 x 250	550 x 650 x 580	4.9	64
FP 1500-9	G14736	9.0	200 x 180 x 250	560 x 720 x 640	6.5	66
FP 1500-15	G15007	15	220 x 220 x 310	590 x 790 x 690	5.8	68
FP 1500-30	G15009	29.7	250 x 270 x 440	660 x 800 x 730	11.5	105

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com

* V 28.01.2022

Specifications subject to change