

Borel

Standard Furnaces & Ovens

since 1918



Photos for illustration purposes only



CHAMBER FURNACES 1600 °C FP 1600

Definition: Electric chamber furnace for all applications, high temperature.

Construction: Robust construction made of bent plate. Vertical lifting front door.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Heating: Silicon carbide heating elements. The heating is turned off at the opening of the door.

Electricity: 3 x 400 VAC.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.

Delivered with: Removable ceramic sole.

MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
FP 1600-5	G15010	5.0	150 x 140 x 250	550 x 650 x 580	5.2	66
FP 1600-9	G15012	8.6	200 x 180 x 250	560 x 720 x 640	5.9	73
FP 1600-15	G15013	15	220 x 220 x 310	590 x 790 x 690	7.0	85
FP 1600-30	G15015	29.7	250 x 270 x 440	660 x 800 x 730	11.5	105

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borel.eu

* V 24.02.2022

Specifications subject to change