

Borel

Standard Furnaces & Ovens

since 1918



Photos for illustration purposes only

CHAMBER FURNACES 1300°C FP 1300

Definition: Electric chamber furnace for all applications.

Construction: Robust construction made of bent plate. Vertical lifting front door.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Aeration: Rear exhaust.

Heating: Coil resistors on ceramic tubes. The heating is turned off at the opening of the door.

Electricity: 18 liters and less, single-phase 230 VAC, 50 Hz. From 25 liters, 3x400 VAC.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.

Delivered with: Removable ceramic sole.



MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
FP 1300-6	G14986	7.0	200 x 140 x 250	550 x 650 x 580	2.45	58
FP 1300-10	G14989	10	200 x 200 x 250	560 x 720 x 640	3.6	67
FP 1300-15	G14990	15	220 x 230 x 300	560 x 790 x 640	3.6	73
FP 1300-30	G14992	30	280 x 280 x 380	590 x 790 x 690	6.0	84
FP 1300-45	G14745	45	300 x 300 x 500	660 x 820 x 810	7.5	114

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com

* V 28.01.2022

Specifications subject to change