

Borel

Standard Furnaces & Ovens

since 1918



ELEVATOR FURNACES

1100-1400°C

LE 1100-1400

Definition: Furnace with rising floor for rapid withdrawing.

Construction: Mechanically welded frame.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Heating: Heating elements surrounded working chamber.

Electricity: Voltage 230 VAC, 50 Hz up to 4.0 kW, and voltage 3x400 VAC, frequency 50 Hz from 4.5 Kw.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.



Photos for illustration purposes only



MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)
LE 1100-8	N16342	7.5	180 x 200 x 210	630 x 1220 x 810	2.0
LE 1400-8	N16343	7.4	180 x 180 x 230	630 x 1220 x 810	4.9

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com

* V 28.01.2022

Specifications subject to change