

# Borel

## Standard Furnaces & Ovens

since 1918



Photos for illustration purposes only

## HIGH TEMPERATURE FURNACES 1700°C MO 1700

**Definition:** Electric chamber furnace for all applications, high temperature.

**Construction:** Robust construction made of bent plate. Vertical lifting front door.

**Insulation:** Multilayer insulation. Interior in ceramic fibre and refractory bricks.

**Heating:** Heating elements type MoSi2. The heating is turned off at the opening of the door.

**Electricity:** Single-phase 230 VAC, 50 Hz up to 7 kW and 3x400 VAC, 50 Hz above 7 kW.

**Regulation:** Axron Swiss PID temperature controller.

**Documentation:** CE marking and operating instructions in English.



MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
MO 1700-2	G15016	2.5	120 x 140 x 150	510 x 770 x 510	3.3	120
MO 1700-4	G15017	3.9	140 x 140 x 200	820 x 660 x 520	4.4	124
MO 1700-8	G15018	8.1	180 x 180 x 250	920 x 700 x 520	7.2	131

**SOLO Swiss SA**

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - [www.borelswiss.com](http://www.borelswiss.com)

\* V 28.01.2022

Specifications subject to change