

Borel

Standard Furnaces & Ovens

since 1918



THERMODRYER OVENS 350°C TR 350

Definition: Forced convection electrical oven for all applications.

Construction: Mild or stainless steel for versions -I, several shelves.

Insulation: Rock wool insulation of all surfaces, including door.

Ventilation: Stainless steel motor ventilator.

Heating: Battery of shielded electrical resistors.

Electricity: Single-phase 230 VAC, 50 Hz.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.

Delivered with: 2 shelves (perforated plates).



Photos for illustration purposes only



MODEL	ITEM CODE	Int. Vol. (L)	Int. Dim. (WxHxD) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
TR 350-58	N16076	58	390 x 360 x 380	675 x 585 x 630	2.0	40
TR 350-58-I	G200218	58	390 x 360 x 380	675 x 585 x 630	2.0	40

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com

* V 28.01.2022

Specifications subject to change