



TUBE FURNACES 1600°C TU 1600

Definition: Tubular electric furnace, for all applications.

Construction: Robust construction made of bent plate.

Insulation: Multilayer insulation. Interior in ceramic fibre and refractory bricks.

Heating: Heating elements in silicon carbide.

Electricity: 3x400 VAC.

Regulation: Axron Swiss PID temperature controller.

Documentation: CE marking and operating instructions in English.



Photos for illustration purposes only

MODEL	ITEM CODE	Heated Length (mm)	Tube Dim. (Øxlength) (mm)	Ext. Dim. (WxHxD) (mm)	Power (kW)	Weight (kg)
TU 1600-50-250	N16200	250	50 x 800	665 x 675 x 400	4.0	46
TU 1600-50-450	N16202	450	50 x 1000	850 x 745 x 400	5.5	48
TU 1600-75-450	G15046	450	75 x 1000	850 x 745 x 400	6.5	73
TU 1600-50-610	N16204	610	50 x 1300	1150 x 745 x 400	6.0	52
TU 1600-75-610	N17936	610	75 x 1300	1150 x 745 x 400	7.5	85

SOLO Swiss SA

Grandes-Vies 25, 2900 Porrentruy, Switzerland - Tel. +41 (0)32 756 64 00 - borel@soloswiss.com - www.borelswiss.com